

4700 SPORTINGUM

Coating for sport floorings

Version 01.00

Date 19.01.2007

DESCRIPTION: Coating based on special rubber resins and copolymers soluble in the solvent. It has a high covering power, resistant to wear and not shiny.

USE: Suitable for painting on the outside of tennis courts, volleyball, basketball, etc.. The ease of application of SPORTINGUM allows a high-speed shutter with the subsequent treatment of large areas for worker/hour. This fact is reflected positively in the economic evaluation of the product. If we consider that the floor can be walked on after 24 hours and that its maintenance is limited to regular cleaning, stands out even more its affordability and functionality.

APPLICATION: By brush or roller.

DILUTION: Thinner 7008: 5%

DRYING TIME: 30' dust dry at 20°C
3 h touch dry at 20°C
24 h total dry at 20°C

COVERING: 4-6 squares meters per kilo depending on the funds.

VISCOSITY: 18-20" Ford Cup 8 at 20°C

SPECIFIC WEIGHT: 1,400 kg/lt at 20°C

USEFUL HINTS: The SPORTINGUM should be applied to dry surfaces. On excessively absorbent surfaces, we recommend a coat of 3906 ISOLRUBBER. Between one hand and the other is good practice to leave an interval of time of 12/24 hours.

**PIT
COLOR**

Rivestimenti Epossidici Prodotti Speciali Vernici isolanti

Via Pietro da Lissone 22/A 20851 LISSONE MB Italy Tel +39.039.482560

www.pitcolor.it email: info@pitcolor.it

Il nostro SERVIZIO TECNICO è a disposizione dei clienti e può fornire in qualsiasi momento una tempestiva assistenza in relazione ad applicazioni di carattere particolare ed a problemi specifici.